# SCX-4623F



# Mono Laser Print, Copy, Scan, Fax MFP



#### Features:

- ESP Easy Screen Print button lets you print either your desktop or just the active window at the touch of a button
- Fast print speeds of up to 23 ppm
- · Fax to PC adds convenience and security
- · ID card copy, clone copy, poster copy and more
- 12,000 page monthly duty cycle
- · High-speed USB 2.0 connectivity
- Quiet operation of under 50dBA
- · Stylish, compact design



SCX-4623F

If you can see it, you can print it. With the Samsung SCX-4623F mono laser MFP, you simply press the ESP Easy Screen Print button, and you can print either your entire desktop or just the active window. That's especially convenient for printing multiple web pages. Samsung's included AnyWeb Print software lets you select, drag and drop content from different web pages into a new page, then print your screen. You also get faxing to and from your PC, print speeds of 23 ppm, 12,000 page monthly duty cycle and a sleek, compact design. The SCX-4623F mono laser MFP from Samsung.



1<sup>er</sup> site Français spécialiste **en photocopieur** et **solution bureautique** Location - Achat - Leasing - Entretien - Maintenance

○ COUVERTURE NATIONALE 
 PRÉSERVÉ AUX PROS 
 SERVICE 100% GRATUIT 
 SIMPLE ET RAPIDE



Ce modèle de photocopieur vous intéresse ? Vous souhaitez obtenir plus d'information ?

Entrez en relation avec un distributeur agréé dans votre département

RÉALISEZ UNE DEMANDE DE DEVIS Gratuit et sans engagement

# SCX-4623F



Mono Laser Print, Scan, Copy, Fax MFP

### Features

#### **ESP Easy Screen Print Button**

Press the Easy Screen Print button, and the SCX-4623F will print your monitor's desktop. Hold it down for two seconds, and it'll print just the active window. It's handy for printing multiple web pages at once.

#### Versatile Copy Features

Features like ID card copy (front and back on one side of the page), clone copy (multiple images on a single sheet) and poster copy (one image on multiple sheets) save you time.

#### Fax to PC

You can send and receive to and from PCs. It adds convenience, uses fewer resources and increases security.

### **Fast Print Speeds**

You don't have to wait. The SCX-4623F gives you print speeds of up to 23 ppm.

# 12,000 Page Monthly Duty Cycle

The 12,000 page duty cycle means reliable Samsung operation.

## Stylish, Compact Design

The SCX-4623F features a sleek, streamlined design that adds sophistication without taking up much office space.

#### SCX-4623F Dimensions



Specifications         SCA-6202F           Print         Final           Specification         Up to 1,200 x 1,200 dpt effective output           Resolution         Up to 1,200 x 1,200 dpt effective output           Final Flage Dut Time         Less than 9 seconds from Ready Modoly           Envalation         SPL Sammarp Print Language)           Objects         Manual           Copy         Second Text (Second Control of Line Strong Print Language)           Steed         Lot 10 23 cpm in Letter           Resolution         Up to 1,200 x 1,200 dpt effective output           First Copy Out Time         Less than 12 seconds (Lines than 14 seconds (ADF)           Zoom Rase         25 - 4,000 x 1,200 dpt effective output           First Copy Out Time         Less than 12 seconds (Lines than 14 seconds (ADF)           Scan Rase         25 - 4,000 x 1,200 dpt effective output           Resolution         Up 0 pages           Corp relativity         1799 pages           Scan Rase         25 - 4,000 x 1,000 dpt           Scan In         PC           Feeduries         1790 x 1,000 x 1,000 dpt           Scan In         PC         PC           Feeduries         1791 x 6,000 x 1,000 dpt           Recolution         300 x 300 dpt         Autor (Second			
Speed         Up to 23 pm in Latter           Resolution         Up to 1,200 x 1,200 for lefective output           First Rage Out Time         Uses transump Print Languages           Duples         Avaination           SPECT (Sumsump Print Languages)           Output           Speed           Up to 1 200 x 1,200 dig reflective output           Test Corp / Un Time         Les than 12 seconds, Less than 14 seconds (ADF)           Zoom Rate         25 - 400%         Month Copy         1999 pages           Copy Features         10 Copy, 2-up, 4-up, Poster Copy, Core Copy, Collation, Auto-16         Secondary           Compatibility         1999 pages           Compatibility         1999 pages         Cover CIS           Resolution         Up 6 4,800 x 4,800 dpl           Scan to         PC         Cover CIS           Resolution         Up 10 G 5,800 x 4,800 dpl           Scan to         PC         Forestater           Forestater           Resolution         300 x 300 dpl           Memory         40% 1225 pages         Forestater           Resolution         250 - sheet Face down, 1 - sheet Face Up         Cover designed fac <th col<="" th=""><th>Specifications</th><th>SCX-4623F</th></th>	<th>Specifications</th> <th>SCX-4623F</th>	Specifications	SCX-4623F
Resolution         Up to 1,200 x 1,200 dpt effective output           First Page Out Time         Less than 9 seconds (from Ready Mode)           Entralation         SPL (Samsung Print Language)           Duplex         Manual           Soper         Manual           Specifical         Up to 23 cpm in Letter           Resolution         Up to 1,200 x 1,200 dpt effective output           First Copy Out Time         Less than 12 seconds; Less than 14 seconds (ADF)           Zoom Rate         25 - 400%           Multi Copy         1-9 pages           Copy Features         10 Copy, 2-up, 4-up, Poster Copy, Collation, Auto-It           Sam         Toward Standard, WA Standard           Webbox         Color GS           Resolution         Up to 4,800 x 4,800 dpl           Scan to         PC           Scan to         PC           Resolution         30 x 500 dpl           Resolution         30 x 500 dpl           Resolution         30 x 500 dpl           Face features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, debayed fax           Pace Features         Speed dial 220 locations, Multi-sending, Fax to PC/PC Fax, debayed fax           Pace Features         Speed dial 250, JiS, BS, Executive, Letter, Ofticio, Folio, Legal, Envelope, Postcard (4"	Print		
First Page Out Time	Speed	Up to 23 ppm in Letter	
Emulation SPL (Samsung Print Language)  Dupiox Manual  Amount Speed Up to 23 cpm in Letter  Pesculation Up to 1.200 x 1,200 x 1,200 dpt effective output.  First Copy Out Time Less than 12 seconds; Less than 14 seconds (ADF)  Zoom Ratu 25 - 40%  Mutit Copy 1-99 pages  Copy Features Dopp 2-up .4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy Out Time Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Collation, Auto-fit  Second Test Copy 1-00 -4-up Poster Copy, Coine Copy, Co	Resolution	Up to 1,200 x 1,200 dpi effective output	
Duplex	First Page Out Time	Less than 9 seconds (from Ready Mode)	
Cocy           Speed         Up to 23 cpm in letter           Resolution         Up to 1,200 x 1,200 dpi effective output           First Copy Out Time         Liss than 12 seconds; Less than 14 seconds (ADF)           Zoom Rate         25 - 400%           Multi Copy         1-99 pages           Copy Features         ID Copy, 2-up, 4-up, Poster Copy, Cone Copy, Coliation, Auto-fit           Sean         TOTAL           Compatibility         TWAIN Standard, Wilk Standard           Method         Color CIS           Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Fox         Compatibility/Modern Speed           ITU-T G3, ECM / 33.6 Ktps           Resolution         30 x 300 dpi           Memory         4 M6 (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PCPC Fax, delayed fax           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PCPC Fax, delayed fax           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PCPC Fax, delayed fax           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PCPC Fax, delayed fax           Bandard Cassette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Fax down, 1-	Emulation	SPL (Samsung Print Language)	
Speed         Up to 23 cpm in Letter           Resolution         Up to 1,200 x 1,200 dpi effective output           First Copy Out Time         Less than 12 seconds; Less than 14 seconds (ADF)           Zoom Rate         25 - 400%           Multi Copy         1-99 pages           Corpy Features         Doby, 2-up, 4-up, Poster Copy, Cone Copy, Collation, Auto-fit           Scan         Toward           Corpetibility         TWANN Standard, WIA Standard           Method         Color CIS           Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Face Team         300 x 300 dpi           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Face Features         300 x 300 dpi           Pace Features         300 sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80 -sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80 -sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80 -sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80 -sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80 -sheet Cassette Tray, 1-sheet Manual Tray           Media Size         A4, A5, ISO, B5, JS, B6, Executive, Letter, Oficio,	Duplex	Manual	
Resolution         Up to 1,200 x 1,200 dpi effective output           First Copy Out Time         Less than 12 seconds; Less than 14 seconds (ADF)           Zoom Rate         2 5 - 400%           25 - 400%         25 - 400%           Multit Copy         1-99 pages           Copy Features         ID Copy, 2-up, 4-up, Poster Copy, Coine Copy, Coliation, Auto-fit           Seat         TVAIN Standard, WA Standard           Method         Color OS           Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Fax         Factor           Compatibility/Modern Speed         TIU-T G3, ECM / 3.6 Kbps           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Fax Features         Speed idal 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Poper Handling         Ago -sheet Face down, 1 -sheet Face up           Media Size         A4, A5, ISO, BS, US, BS, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4* x 6*), Custom           Media Type         Prian, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Size         Width: 5.6* - 8.5* / Length: 5.8* - 1.4*           Resolution         Windows 2000/APV/staz2003 Server/Zools Server, Various Linux OS, Mac OS X 10.3 - 10.6<	Сору		
First Copy Out Time         Less than 12 seconds; Less than 14 seconds (ADF)           Zoom Rate         25 - 400%           Multi Copy         1-99 pages           Copy Features         D Copy, 2-up, 4-up, Poster Copy, Clone Copy, Collation, Auto-fit           Scan         Compatibility         TWAIN Standard, WMS Standard           Method         Color CS           Resolution         Up to 4.800 x 4.800 dpl           Scan to         PC           Fax         Compatibility/Modern Speed         TU-T G3, ECM / 33.6 Kbps           Resolution         300 x 300 dpl           Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling         Standard Cassette           Standard Cassette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Medial Size         A4, A5, S0, Bis, XB, Sb, Executive, Letter, Officio, Folio, Legal, Envelope, Postaard (4* x 6*), Custom           Medial Type         Pfain, Thick, Thin, Cotton, Coloned, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Size         A5, SV, Bis, XB, Sb, Executive, Letter, Officio, Folio, Legal, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Size         A6,	Speed	Up to 23 cpm in Letter	
Zoom Rate         25 - 400%           Multi Cory         1-99 pages           Copy Features         ID Copy, 2-up, 4-up, Poster Copy, Cone Copy, Collation, Auto-fit           Scan         TWAIN Standard, WMA Standard           Compatibility         TWAIN Standard, WMA Standard           Method         Color CS           Resolution         Up to 4,800 x 4,800 dpl           Scan to         FO           Fax         For Peatures           Compatibility/Modem Speed         ITU-T G3, ECM / 33.6 Kbps           Resolution         300 x 300 dpl           Memory         4 MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling         Fax features           Standard Cassette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Type         Plain, Thick, Thin, Cotton, Cotored, Pre-printed, Recycled, Envelope, Postcard (4" x 6"), Custom           Media Type         Plain, Thick, Thin, Cotton, Cotored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Size         Width 5.6" - 8.5" / Length: 5.8" - 1.4"           General         LD           LOD         2 line x 16 characters <tr< td=""><td>Resolution</td><td>Up to 1,200 x 1,200 dpi effective output</td></tr<>	Resolution	Up to 1,200 x 1,200 dpi effective output	
Multi Copy         1-99 pages           Copy Features         ID Copy, 2-up, 4-up, Poster Copy, Clone Copy, Collation, Auto-fit           Scar           Scan           Compatibility         TWAIN Standard, WIA Standard           Method         Color CIS           Resolution         Up to 4,800 x 4,800 dpl           Scan to         PC           Fox         TUTT G3, ECM / 33.6 Kbps           Resolution         300 x 300 dpl           Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Poper Human         Standard Cassette         250 -sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, B5, JIS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Type         Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Capacity         40 sheets           AGC Size         40 sheets           AGC Size         40 sheets           AGC Size         40 sheets           Agency         40 sheets           Agency         40 sheets           Agency	First Copy Out Time	Less than 12 seconds; Less than 14 seconds (ADF)	
Corp         Corp <t< td=""><td>Zoom Rate</td><td>25 - 400%</td></t<>	Zoom Rate	25 - 400%	
Scale         Compatibility         TWAIN Standard, WIA Standard           Method         Coir CIS           Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Fax           Compatibility/Modem Speed           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Eax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Pager Handling           Standard Cassette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, B5, JIS, B5, Executive, Letter, Offcio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Size         A4, A5, ISO, B5, JIS, B5, Executive, Letter, Offcio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           ADC Size         Width: 5.6" -8.5" / Length: 5.8" - 14"           General           LDD         2 line x 16 characters           Processor         360 MHz           Memory         64MB           OS Compatibility         Windows 2000/Pr/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3-10.6           Interface         Hi-Speed USB 2.0	Multi Copy	1-99 pages	
Compatibility         TWAIN Standard, WIA Standard           Method         Color CIS           Resolution         Up to 4,800 x 4,800 dpl           Scan to         PC           Fax         PC           Campatability/Modem Speed         ITU-T G3, ECM / 33.6 Kbps           Resolution         300 x 300 dpl           Memory         4MB (225 pages)           Fax Features         Speed dal 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Poper Handling         ************************************	Copy Features	ID Copy, 2-up, 4-up, Poster Copy, Clone Copy, Collation, Auto-fit	
Method         Coior CIS           Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Fax         TU-T G3, ECM / 33.6 Kbps           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Reparterar Classette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Type         Plain, Thick, Thin, Cottor, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardistock, Bond, Archive           ADF Capacity         40 sheets           ADC Gize         Width: 5.6° - 8.5° / Length: 5.8° - 14°           General         Uiden: 5.6° - 8.5° / Length: 5.8° - 14°           Memory         64MB           OS Compatibility         Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3-10.6           Interface         Hi-Speed USB 2.0           Noise Level         Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)           Duty Cycle         12.6° x 16.4° x 16.1°           Weight (w foner)         25.4 lbs           Supplies           Toner         Standard-yield black toner cartridge 1,500 pages (MLT-D105S) <td>Scan</td> <td></td>	Scan		
Resolution         Up to 4,800 x 4,800 dpi           Scan to         PC           Fax           Compatibility/Modem Speed         ITU-T G3, ECM / 33.6 kbps           Resolution         300 x 300 dpi           Memony         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Poper Handling         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, BS, JS, BS, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Type         Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADF Capacity         40 sheets           ADC Size         Width: 5.6" - 8.5" / Length: 5.8" - 14"           General         UCD         2 line x 16 characters           Processor         350 MHz           Memory         64MB           OS Compatibility         Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3-10.6           Interface         Hi-Speed USB 2.0           Noise Level         Less than 50 oB (Printing, Copying); Less than 52 d	Compatibility	TWAIN Standard, WIA Standard	
Scan to         PC           Fix         Compatibility/Modem Speed         ITU-T G3, ECM / 33.6 Kbps           Resolution         30 x B 202 bagies           Fax Features         Speed dial 2000 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling         Fax Features           Poper Handling         250-sheet Cassette Tray, 1-sheet Manual Tray           Standard Cassette         250-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, B5, JS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Tape         Plain, Thick, Tootron, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADF Capacity         40 width: 5.6" - 8.5" / Length: 5.8" - 14"           General         Concessor         360 MHz           Memory         64MB           OS Compatibility         Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3-10.6           Interface         Hi-Speed USB 2.0           Notise Level         Hi-Speed USB 2.0           Dimension (H x W x D)         12.6" x 16.4" x 16.1"           Weight (W toner)         25.4 lbs           Supplies           Toner         Standard-yield black toner cartridge 1,500 pages (MLT-D10S)         Hi-Speed Leded cartridge yield in accordance wi	Method	Color CIS	
Fax         Compatibility/Modem Speed         ITU-T G3, ECM / 33.6 kbps           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling           Standard Cassette           250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, 95, JIS, 85, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Tipe         Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Capacity         40 sheets           ADC Size         Width: 5.6" - 8.5" / Length: 5.8" - 14"           General           LCD         2 line x 16 characters           Processor         360 MHz           Memory         64MB           OS Compatibility         Windows 2000/XP/vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6           Interface         Hi-Speed USB 2.0           Noise Level         Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)           Duty Cycle         12.6" x 16.4" x 16.1"           Weight (w/ toner)	Resolution	Up to 4,800 x 4,800 dpi	
Compatibility/Modem Speed         ITU-T 63, ECM / 33.6 kbps           Resolution         300 x 300 dpi           Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Pager Handling           Standard Cassette           250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, B5, JIS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custorn           Media Type         Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADF Capacity         40 sheets           ADC Size         Wirdth: 5.6" - 8.5" / Length: 5.8" - 14"           General           LCD         2 line x 16 characters           Processor         360 MHz           Memory         64MB           OS Compatibility         Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3 - 10.6           Interface         Hi-Speed USB 2.0           Noise Level         Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)           Duty Cycle         12.0" x 16.4" x 16.1"           Weight (w/ toner)         25 tan	Scan to	PC	
Resolution     300 x 300 dpi       Memory     4MB (225 pages)       Fax Features     Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax       Paper Handling       Standard Cassette     250-sheet Cassette Tray, 1-sheet Manual Tray       Output Tray     80-sheet Face down, 1-sheet Face up       Media Size     A4, A5, ISO, B5, JIS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom       Media Type     Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive       ADF Capacity     40 sheets       ADC Size     Width: 5.6" - 8.5" / Length: 5.8" - 14"       Ceneral       LCD     2 line x 16 characters       Processor     360 MHz       Memory     64MB       OS Compatibility     Windows 2000/XPA/ista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3-10.6       Interface     Hi-Speed USB 2.0       Noise Level     Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)       Duty Cycle     12,000 pages       Dimension (H x W x D)     12.6" x 16.4" x 16.1"       Weight (w/ toner)     25.4 lbs       Supplies       Toner     Standard-yield black toner cartridge 1,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page	Fax		
Memory         4MB (225 pages)           Fax Features         Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax           Paper Handling           Standard Cassette         250-sheet Cassette Tray, 1-sheet Manual Tray           Output Tray         80-sheet Face down, 1-sheet Face up           Media Size         A4, A5, ISO, B5, JIS, B5, Executive, Letter, Oficio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom           Media Type         Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive           ADC Capacity         40 sheets           ADC Size         Width: 5.6" - 8.5" / Length: 5.8" - 14"           General         LCD         2 line x 16 characters           Processor         360 MHz           Memory         64MB           OS Compatibility         Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6           Interface         Hi-Speed USB 2.0           Noise Level         Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)           Duty Cycle         12.000 pages           Dimension (H x W x D)         12.6" x 16.4" x 16.1"           Weight (w/ toner)         25.4 lbs           Supplies           Toner         Standard-yield blac	Compatibility/Modem Speed	ITU-T G3, ECM / 33.6 Kbps	
Fax Features Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax  Paper Handling  Standard Cassette 250-sheet Cassette Tray, 1-sheet Manual Tray  80-sheet Face down, 1-sheet Face up  Media Size A4, A5, ISO, B5, JIS, B5, Executive, Letter, Oficio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom  Media Type Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive  ADF Capacity 40 sheets  ADC Size Width: 5.6" - 8.5" / Length: 5.8" - 14"  General  LCD 2 line x 16 characters  Processor 360 MHz  Memory 64MB  OS Compatibility Windows 2000/XPA/vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Resolution	300 x 300 dpi	
Paper Handling         Standard Cassette       250-sheet Cassette Tray, 1-sheet Manual Tray         Output Tray       80-sheet Face down, 1-sheet Face up         Media Size       A4, A5, ISO, B5, JIS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom         Media Type       Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive         ADF Capacity       40 sheets         ADC Size       Width: 5.6" - 8.5" / Length: 5.8" - 14"         General       LCD         LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Supplies         Toner       Standard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105S)         Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter to	Memory	4MB (225 pages)	
Standard Cassette 250-sheet Cassette Tray, 1-sheet Manual Tray  Output Tray 80-sheet Face down, 1-sheet Face up  Media Size A4, A5, ISO, B5, JIS, B5, Executive, Letter, Officio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom  Media Type Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive  ADF Capacity 40 sheets  ADC Size Wirdth: 5.6" - 8.5" / Length: 5.8" - 14"  General  LCD 2 line x 16 characters  Processor 360 MHz  Memory 64MB  OS Compatibility Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant ■	Fax Features	Speed dial 200 locations, Multi-sending, Fax to PC/PC Fax, delayed fax	
Output Tray       80-sheet Face down, 1-sheet Face up         Media Size       A4, A5, ISO, B5, JIS, B5, Executive, Letter, Oficio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom         Media Type       Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive         ADF Capacity       40 sheets         ADC Size       Width: 5.6" - 8.5" / Length: 5.8" - 14"         General         LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Supplies         Toner       Standard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)         Green Management         Power Consumption       Sleep Mode: less than 10W; Ready: less than	Paper Handling		
Media Size       A4, A5, ISO, B5, JIS, B5, Executive, Letter, Oficio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom         Media Type       Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive         ADF Capacity       40 sheets         ADC Size       Width: 5.6" - 8.5" / Length: 5.8" - 14"         General       Ceneral         LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XPA/ista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Supplies         Toner       Standard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)         Green Management       Power Consumption       Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W	Standard Cassette	250-sheet Cassette Tray, 1-sheet Manual Tray	
Media Type Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive  ADF Capacity 40 sheets  Width: 5.6" - 8.5" / Length: 5.8" - 14"  General  LCD 2 line x 16 characters  Processor 360 MHz  Memory 64MB  OS Compatibility Windows 2000/XP/Nista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant ■	Output Tray	80-sheet Face down, 1-sheet Face up	
ADF Capacity 40 sheets  ADC Size Width: 5.6" - 8.5" / Length: 5.8" - 14"  General  LCD 2 line x 16 characters  Processor 360 MHz  Memory 64MB  OS Compatibility Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W	Media Size	A4, A5, ISO, B5, JIS, B5, Executive, Letter, Oficio, Folio, Legal, Envelope, Postcard (4" x 6"), Custom	
ADC Size       Width: 5.6" - 8.5" / Length: 5.8" - 14"         General         LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Sundard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)         Green Management         Power Consumption       Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W         Energy-Star Compliant       ■	Media Type	Plain, Thick, Thin, Cotton, Colored, Pre-printed, Recycled, Envelope, Transparency, Label, Cardstock, Bond, Archive	
Ceneral         LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Supplies         Toner       Standard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)         Green Management         Power Consumption       Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W         Energy-Star Compliant       ■	ADF Capacity	40 sheets	
LCD       2 line x 16 characters         Processor       360 MHz         Memory       64MB         OS Compatibility       Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6         Interface       Hi-Speed USB 2.0         Noise Level       Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)         Duty Cycle       12,000 pages         Dimension (H x W x D)       12.6" x 16.4" x 16.1"         Weight (w/ toner)       25.4 lbs         Supplies         Toner       Standard-yield black toner cartridge 1,500 pages (MLT-D105S)         High-yield black toner cartridge 2,500 pages (MLT-D105L)       Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)         Green Management         Power Consumption       Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W         Energy-Star Compliant       ■	ADC Size	Width: 5.6" - 8.5" / Length: 5.8" - 14"	
Processor 360 MHz  Memory 64MB  OS Compatibility Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	General		
Memory 64MB  OS Compatibility Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6  Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	LCD	2 line x 16 characters	
OS Compatibility Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6 Interface Hi-Speed USB 2.0 Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S) High-yield black toner cartridge 2,500 pages (MLT-D105L) Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Processor	360 MHz	
Interface Hi-Speed USB 2.0  Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Memory	64MB	
Noise Level Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)  Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S) High-yield black toner cartridge 2,500 pages (MLT-D105L) Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	OS Compatibility	Windows 2000/XP/Vista/2003 Server/2008 Server, Various Linux OS, Mac OS X 10.3~10.6	
Duty Cycle 12,000 pages  Dimension (H x W x D) 12.6" x 16.4" x 16.1"  Weight (w/ toner) 25.4 lbs  Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Interface	Hi-Speed USB 2.0	
Dimension (H x W x D)  12.6" x 16.4" x 16.1"  Weight (w/ toner)  25.4 lbs  Supplies  Toner  Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption  Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Noise Level	Less than 50 dB (Printing, Copying); Less than 52 dB (ADF); Less than 26 dB (Standby)	
Weight (w/ toner)  25.4 lbs  Supplies  Toner  Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption  Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Duty Cycle	12,000 pages	
Supplies  Toner Standard-yield black toner cartridge 1,500 pages (MLT-D105S) High-yield black toner cartridge 2,500 pages (MLT-D105L) Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Dimension (H x W x D)	12.6" x 16.4" x 16.1"	
Toner  Standard-yield black toner cartridge 1,500 pages (MLT-D105S)  High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption  Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Weight (w/ toner)	25.4 lbs	
High-yield black toner cartridge 2,500 pages (MLT-D105L)  Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption  Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Supplies		
Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)  Green Management  Power Consumption  Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant	Toner	Standard-yield black toner cartridge 1,500 pages (MLT-D105S)	
Green Management       Power Consumption     Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W       Energy-Star Compliant     ■		High-yield black toner cartridge 2,500 pages (MLT-D105L)	
Power Consumption Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W  Energy-Star Compliant		Declared cartridge yield in accordance with ISO/IEC 19752 (Ships with 1,000 page starter toner cartridge)	
Energy-Star Compliant	Green Management		
	Power Consumption	Sleep Mode: less than 10W; Ready: less than 45W; Average: 370W	
Star Recycle Program	Energy-Star Compliant		
	Star Recycle Program		



